

Boreart Sherbrooke Series




Combining acoustic performance and architectural design, the Sherbrooke Series offers high-end soundproofing panels designed for interior walls and ceilings. Thanks to their sound absorption capacity, they eliminate reverberation and ensure optimal acoustic comfort. Easy to install, these panels are composed of a high-quality real wood veneer laminated onto natural or black MDF for an elegant and durable finish.



CHARACTERISTICS

Type	Boréart Sherbrooke Series (acoustic option)
Melamine	Two (2) standard melamines, White Oak and Black Walnut – other melamines available upon request
Nominal panel size	24" x 24" 24" x 48"
Panel material	Natural or black MDF – Fire resistant
Size and spacing of slats	One size fits all. See drawings.
Acoustic material	Polyester and recycled plastic felt – 0.35 to 1 inch – 33 color choices, see page 3. Noise Reduction Coefficient (NRC) up to 0.70 to 0.95.
Fire resistance	ASTM E-84 – Class A Class 1 Flame spread index = 0-25, smoke production index = 450 max NAF
Environment	Made from 100% pre-consumer recycled wood, FSC® certified, and subject to an NAF (no added formaldehyde) exemption.
Use	Interior; residential, commercial, and institutional
Installation	Rigid panels and easy installation Vertical or horizontal installation For interior walls and ceilings
Others	High-performance acoustic properties offering excellent sound reduction Finishing moldings available

SHERBROOKE SERIES PANEL WITH QUOTATIONS



Acoustic material

Felt - Fire resistant

Size 24" x 24" | 24" x 48"

Thickness 9 mm
12 mm
25,4 mm

Panel weight

11,42 lbs | 22,84 lbs

Panel area

4 ft² | 8 ft²

MELAMINES



01 Brushed Bleached Elm



02 White Oak



03 Ash Walnut



04 Black Walnut



05 Brushed Ash Elm



06 Black Brushed Elm




07 Brushed Grey Elm

*Please note that the colors shown may differ slightly from the actual colors due to variations in display rendering. For more details, please contact Boreart.


FELT




White




Yellow



Orange



Mango



Bright red




Dark red




Burgundy



Fuchsia




Pink



Lavender




Purple



Green apple




Olive



Kelly green




Teal




Forest green



Light blue



Blue



Electric blue



Dark blue



Light brown



Coffee



Chocolate



Light grey



Dark grey



Black

*Please note that the colors shown may differ slightly from the actual colors due to variations in display rendering. For more details, please contact Boreart.

WARRANTY

Boreart offers a 5-year warranty on all its panels. For more details on the limited warranty, please contact Boreart.

SHIPPING

Boreart products are packaged and shipped in wooden crates and/or on 4' x4' wooden pallets.

USE & STORAGE

Wood products are hygroscopic by nature and must be installed flat and maintained in a building with a controlled environment. The temperature must be maintained between 15° and 30°C. Relative humidity must be maintained between 25% and 55%.

The advice and recommendations are purely advisory.

Handling and storage - melamine sheets must be stored in such a way as to protect them from moisture and direct sunlight. Melamine sheets should preferably be stored face to face or with the decorative side facing up, flat, completely horizontal, and level.

When handling or moving melamine, it is important that the sheets are lifted above the adjacent sheets to avoid damage that may occur if the sheets are pulled or slid against each other. For larger formats, it is recommended that arched sheets be carried along the longitudinal axis to prevent sagging. Individual sheets can also be rolled up for easier handling.

Failure to comply with one or more of the above conditions will void the Boréart Architectural Products warranty.

INSTALLATION

For more details, please refer to the Boreart Sherbrooke Series installation guide on the website.

HOW TO ORDER

To order a product, please write to **info@boreart.ca** using the following template to ensure maximum accuracy.

The first three characters are the model code, followed by the melamine code, the desired dimensions, the color of the felt as a whole, and the last letters represent the thickness of the felt.



Pattern

Sherbrooke : SHE

Colors

See page 3 for the 33 felt color choices.

Thickness

9 mm
12 mm
25,4 mm

Melamines

Brushed Bleached Elm :	OBB
White Oak :	CBL
Ash Walnut :	NCD
Black Walnut :	NNR
Brushed Ash Elm :	OBC
Black Brushed Elm :	OBN
Brushed Grey Elm :	OBG